

Product data sheet

Specifications



Motor mechanism,
110...230VAC@50/60Hz,
110...230VDC

LV435010

Main

Range	EasyPact
product name	EasyPact CVS
Product or component type	Motor mechanism
Device short name	motor mechanism module
Product compatibility	EasyPact CVS400...630 circuit-breaker

Complementary

Control type	Local/remote control
Control signal type	Impulse and maintained
[Uc] control circuit voltage	110...230 V AC 50/60 Hz 110...230 V DC
Mounting mode	Fixed
Response time	<= 500 ms (opening) <= 1 s (closing)
Maximum operating frequency	<= 2 cycles per minute
Maximum power consumption in VA	300 VA closing 300 VA opening
Electrical durability	20000 cycles 110...230 V AC 50/60 Hz 20000 cycles 110...230 V DC
Provided equipment	Keylock
Locking options description	Transparent cover
IK degree of protection	IK07

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.000 cm
Package 1 Width	2.000 cm
Package 1 Length	22.000 cm
Package 1 Weight	2.923 kg
Unit Type of Package 2	S04
Number of Units in Package 2	3
Package 2 Height	30.000 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	9.389 kg
Unit Type of Package 3	P12
Number of Units in Package 3	36
Package 3 Height	105.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	129.096 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile
Use Better	
Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
Use Again	
Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No